MATERIAL SAFETY DATA SHEET STYRENE (MONOMER) MSDS

1: Chemical Product and Company Identification

Product Name: Styrene (monomer)
Catalogue Codes: SLS2512, SLU1027

CAS#: 100-42-5 RTECS: WL3675000

TSCA: TSCA 8(b) inventory: Styrene (monomer)

CI#: Not available. Synonym: Vinylbenzene

Chemical Formula: C8H8

2: Composition and Information on Ingredients

Composition:

Name	CAS#	% by Weight
Styrene (monomer)	100-42-5	100

Toxicological Data on Ingredients: Styrene (monomer): ORAL (LD50): Acute: 2650 mg/kg [Rat]. 316 mg/kg [Mouse].

VAPOR (LC50): Acute: 12000 ppm 4 hour(s) [Rat]. 9500 ppm 4 hour(s) [Mouse].

3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of eye contact (irritant). Hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation. Inflammation of the eye is characterized by redness, watering, and itching.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Classified + (PROVEN) by OSHA. Classified 2B (Possible for human.) by IARC. A4 (Not

classifiable for human or animal.) by ACGIH.

MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to the nervous system, upper respiratory tract.

Repeated or prolonged exposure to the substance can produce target organs damage.

4: First Aid Measures

Eve Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids_open. Cold water may be used. Do not use an eye ointment. Seek medical attention.

Skin Contact:

After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

<u>Inhalation:</u> Allow the victim to rest in a well-ventilated area. Seek immediate medical attention.

Serious Inhalation: Not available.

Ingestion:

Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Serious Ingestion: Not available.

5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 490°C (914°F)

Flash Points: CLOSED CUP: 31.1°C (88°F).

(Cleveland) OPEN CUP: 36.7°C (98.1°F) (TAG).

Flammable Limits: LOWER: 1.1% UPPER: 6.1%

Products of Combustion: These products are carbon oxides

(CO, CO2).

Fire Hazards in Presence of Various Substances:

Flammable in presence of open flames and sparks. Slightly flammable to flammable in presence of

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available.

Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet to prevent pressure build-up, autoignition or explosion.

Special Remarks on Fire Hazards:

Special Remarks on Explosion Hazards:

Not available.

Not available.

6: Accidental Release Measures

Small Spill:

Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:

Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7: Handling and Storage

Precautions:

Keep locked up Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do

not ingest. Do not breathe gas/fumes/ vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes

Storage:

Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective

threshold limit value. Ensure that eyewash stations and safety showers are proximal to the workstation location.

Personal Protection:

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 50 STEL: 100 (ppm) TWA: 213 STEL: 426 (mg/m3) Consult local authorities for acceptable exposure limits.

9: Physical and Chemical Properties

Physical state and appearance: Liquid. (Clear viscous liquid.)

odour: Sweetish. Aromatic.
Taste: Not available.
Molecular Weight: 104.14 g/mole

Colour:
Colourless.

pH (1% soln/water):

Boiling Point:

Melting Point:

Critical Temperature:

104.14 g/mole
Colourless.

Not available.

145.2°C (293.4°F)

-30.6°C (-23.1°F)

Not available.

Specific Gravity: 0.906 (Water = 1)Vapor Pressure: 4.5 mm of Hg (@ 20°C)

Vapor Density:3.59 (Air = 1)Volatility:Not available.odour Threshold:0.1 ppm

Water/Oil Dist. Coeff.: The product is equally soluble in oil

Iconicity (in Water):

Dispersion Properties:

Not available.

Not available.

Solubility: Very slightly soluble in cold water.

10: Stability and Reactivity Data

and water; log(oil/water) = 0

Stability: The product is stable.

Instability Temperature:

Conditions of Instability:

Incompatibility with various substances:

Not available.

Not available.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Special Remarks on Corrosivity:

Not available.

Polymerization: No.

11: Toxicological Information

Routes of Entry: Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.

Acute oral toxicity (LD50): 316 mg/kg [Mouse]. Acute toxicity of the vapor (LC50): 9500 ppm 4

hour(s) [Mouse].

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified + (PROVEN) by OSHA. Classified 2B (Possible for human.) by IARC. A4 (Not classifiable for human or animal.) by ACGIH. The substance is toxic to the nervous system, upper respiratory tract.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

Animal embryotoxic. Postnatal development injury in animal. Menstrual disorders in human.

Human: passes the placental barrier, detected in maternal milk.

Special Remarks on other Toxic Effects on Humans: Not available.

12: Ecological Information

Ecotoxicity: Not available. BOD5 and COD: Not available. Products of Biodegradation:

Possibly hazardous short-term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

13: Disposal Considerations

Waste Disposal:

14: Transport Information

DOT Classification: Class 3: Flammable liquid.

p. 5

Identification: Styrene monomer, inhibited: UN2055 PG: III

Special Provisions for Transport: Marine Pollutant

15: Other Regulatory Information

Protective Equipment:

Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

16: Other Information

References: Not available.

Other Special Considerations: Not available.

EXCLUSION OF LIABILITY

All information and instructions provided in this Material Safety Data Sheet in respect of the substance is given solely in terms of the provisions of the Occupational Health and Safety Act No 85 of 1993

and Regulations ("the Act"), is based on scientific and technical knowledge as at the date indicated on this MS Material Safety Data Sheet and is presented in good faith to be correct.

The information and instructions provided in this MSDS apply only to the substance in its present form and not to any formulation or mix, in which event it is the sole responsibility of the user of the substance as formulated and/or mixed to investigate and establish any danger which may arise out of its use, wherever such user may be situated.

It is the sole responsibility of the person in receipt of this Material Safety Data Sheet wherever such recipient may be situated, to ensure that the information provided is communicated to and understood by any person who may come in contact with the substance in any place and in any manner whatsoever. If such recipient produces formulations or mixes using the substance, then it is such recipient's sole responsibility to comply with the provisions of the Act in respect of the provision of the necessary Material Safety Data Sheet, or to comply with any other applicable legislation.